

Vannsikker ultralydsensor

Produktkode: 507

Tilgjengelighet: 1

Pris: kr. 250,00



Short Description

ME007-ULS V1 Waterproof Ultrasonic Sensor Module Measuring Range 25cm-8m

Beskrivelse

Features?

- 1) High degree of protection;
- 2) Wide usage range, low-power dissipation;
- 3) Simple to use, handle easily;
- 4) High measuring accuracy and resolution;
- 5) Small detection blind area, long detection range;
- 6) With high precision temperature output and temperature compensation function;
- 7) Varied output mode: serial output, PWM output, digital output;



Applications?

- 1) High precision distance measuring;
- 2) Obstacle-avoidance, automatic control;
- 3) Objects close to, exist, perceive;
- 4) Traffic control;
- 5) Security and protection, industrial control;
- 6) Artificial intelligence, teaching and research;

Electrical parameters?

	PWM output	Serial output	Digital output
Supply voltage	3.3V-12V		
Standby current	Less than 200uA		More than 400uA
Average current	2mA(base on supply voltage is 5V?cycle is 250MS)		
Center frequency	40 KHZ		
Blind zone	200 MM		
Max. detection distance	More than 8M		
Emission angle	8°		
Work cycle	More than 60MS?controlled by the trigger signal		250 MS
Trigger signal	Falling edge?low level keeps 0.1-10MS		GND connection
Test precision	±1CM		
Resolution of ranging	1 MM		
Temperature compensation	Non compensation	compensation	
Temperature output	None	Have	None
Operating temperature	-25?—70?		



